

NORTHEASTERN UNIVERSITY, KHOURY COLLEGE OF COMPUTER SCIENCE

CS 6220 Data Mining — Assignment 2 Due: January 25, 2024(100 points)

YOUR NAME YOUR GIT USERNAME YOUR E-MAIL

Frequent Itemsets

Consider the following set of frequent 3-itemsets:

 $\{1, 2, 3\}, \{1, 2, 4\}, \{1, 2, 5\}, \{1, 3, 4\}, \{2, 3, 4\}, \{2, 3, 5\}, \{3, 4, 5\}.$

Assume that there are only five items in the data set. This question was taken from Tan et al., which may help in reviewing Candidate Generation.

- 1. List all candidate 4-itemsets obtained by a candidate generation procedure using the $F_{k-1} \times F_1$ merging strategy.
- 2. List all candidate 4-itemsets obtained by the candidate generation procedure in A Priori, using $F_{k-1} \times F_{k-1}$.
- 3. List all candidate 4-itemsets that survive the candidate pruning step of the Apriori algorithm.

Association Rules

Consider the following table for question 4:

Transaction ID	Items
1	$\{ Beer, Diapers \}$
2	{Milk, Diapers, Bread, Butter}
3	{Milk, Diapers, Cookies}
4	$\{Bread, Butter, Cookies\}$
5	$\{Milk, Beer, Diapers, Eggs\}$
6	$\{ Beer, Cookies, Diapers \}$
7	{Milk, Diapers, Bread, Butter}
8	$\{ Bread, Butter, Diapers \}$
9	{Bread, Butter, Milk}
10	$\{ Beer, Butter, Cookies \}$

- 4. a) What is the maximum number of association rules that can be extracted from this data (including rules that have zero support)?
 - b) What is the confidence of the rule {Milk, Diapers} \Rightarrow {Butter}?
 - c) What is the support for the rule {Milk, Diapers} \Rightarrow {Butter}?
- 5. True or False with an explanation: Given that $\{a,b,c,d\}$ is a frequent itemset, $\{a,b\}$ is always a frequent itemset.
- 6. True or False with an explanation: Given that $\{a,b\}$, $\{b,c\}$ and $\{a,c\}$ are frequent itemsets, $\{a,b,c\}$ is always frequent.
- 7. True or False with an explanation: Given that the support of $\{a,b\}$ is 20 and the support of $\{b,c\}$ is 30, the support of $\{b\}$ is larger than 20 but smaller than 30.
- 8. True or False with an explanation: In a dataset that has 5 items, the maximum number of size-2 frequent itemsets that can be extracted (assuming minsup > 0) is 20.
- 9. Draw the itemset lattice for the set of unique items $\mathcal{I} = \{a, b, c\}$.